

Instruction Sheet

“Fire prevention – European classification of building products”

European classification of building products

Building authority designation	Additional requirements				Building authority designation	Additional requirements			
	DIN 4102	DIN EN 13501	no smoke	no flaming particles/droplets		DIN 4102	DIN EN 13501	no smoke	no flaming particles/droplets
Non-combustible	A1	A1	yes	yes	Difficult to ignite	B1	A2 - s3,d2		
Non-combustible	A2	A2 - s1,d0	yes	yes	Difficult to ignite	B1	B - s3,d2		
Difficult to ignite	B1	B - s1,d0	yes	yes	Difficult to ignite	B1	C - s3,d2		
Difficult to ignite	B1	C - s1,d0	yes	yes	Normal combustibility	B2	D - s1,d0		yes
Difficult to ignite	B1	A2 - s2,d0		yes	Normal combustibility	B2	D - s2,d0		yes
Difficult to ignite	B1	A2 - s3,d0		yes	Normal combustibility	B2	D - s3,d0		yes
Difficult to ignite	B1	B - s2,d0		yes	Normal combustibility	B2	E		yes
Difficult to ignite	B1	B - s3,d0		yes	Normal combustibility	B2	D - s1,d1		
Difficult to ignite	B1	C - s2,d0		yes	Normal combustibility	B2	D - s2,d1		
Difficult to ignite	B1	C - s3,d0		yes	Normal combustibility	B2	D - s3,d1		
Difficult to ignite	B1	A2 - s1,d1	yes		Normal combustibility	B2	D - s1,d2		
Difficult to ignite	B1	A2 - s1,d2	yes		Normal combustibility	B2	D - s2,d2		
Difficult to ignite	B1	B - s1,d1	yes		Normal combustibility	B2	D - s3,d2		
Difficult to ignite	B1	B - s1,d2	yes		Normal combustibility	B2	E - d2		
Difficult to ignite	B1	C - s1,d1	yes		Normal combustibility	B2	F		
Difficult to ignite	B1	C - s1,d2	yes						

The following conditions apply at NürnbergMesse:

- unrestricted approval
- up to 2.50 m for walls/not approved for overhead use
- not approved
- should be avoided (s3)

Key to building product classes: to DIN 4102

- A1 = non-combustible
- A2 = non-combustible
- B1 = difficult to ignite
- B2 = normal combustibility
- B3 = easily ignited

Key to building product classes: to DIN EN 13501

- A1 = non-combustible
- A2 = non-combustible
- B,C = difficult to ignite
- D,E = normal combustibility
- F = easily ignite
- s1 = no/hardly any smoke production
- s2 = limited smoke production
- s3 = unlimited smoke production
- d0 = no droplets
- d1 = limited droplets
- d2 = many droplets